



PRO SERIES™ Screened Masthead Amplifier Kits

- Fully screened with F-Type connectors and LED indicator
- Kits supplied with 100mA power supply
- Every screened masthead amp has a built in F-box spanner
- Proven weatherproof housing, mast or loft mounting

PRODUCT RANGE

- UXF1-15U - 15dB Screened masthead kit
- UXF1-25U - 25dB Screened masthead kit
- UXF2 - 2 way masthead kit
- UXF4 - 4 way masthead kit

TECHNICAL SPECIFICATION

	UXF1-15	UXF1-25	UXF2	UXF4
No. of Inputs	1	1	1	2
No. of Outputs	1	1	2	4
Frequency range	470-862MHz	470-862MHz	470-862MHz	85-230 / 470-862MHz
Gain	15dB	25dB	10dB	10dB -10dB
Noise Max	<3.0dB	<3.5dB	<3.5dB	<3.5dB
Max. Output*	98dB μ V	102dB μ V	94dB μ V	92dB μ V
Power Requirement	26mA	40mA	40mA	40mA

* DIN 45004B 3 carriers, IMD3 - 60dB

PSF1200

Mains	230V AC \pm 10% 50Hz Fitted Mains Plug BS1363 3A rating
Line Power Out	+ 12V DC (\pm 10%) 100mA
Insertion Loss	<1dB (46-1000MHz)

Fully screened Masthead Power Supply