

UXFR4-20



PSF1200



PRO SERIES™ Screened Variable Masthead Kits

- Variable gain 1 to 20dB gain (UXFR1 1 to 25db)
- Fully screened with F-Type connectors and LED indicator
- Kits supplied with 100mA power supply
- Every screened masthead amp has a built in F-box spanner

PRODUCT RANGE

- UXFR1 - 1-25dB variable masthead kit
- UXFR2-20 - 2-way 1-20dB variable masthead kit
- UXFR4-20 - 4-way 1-20dB variable masthead kit
- UXFR5-20 -5-way 1-20dB variable masthead kit

TECHNICAL SPECIFICATION

	UXFR1	UXFR2-20	UXFR4-20	UXFR5-20
No. of Inputs	1	1	2	1
No. of Outputs	1	2	4	5
Frequency range	470-862MHz	470-862MHz	85-230 / 470-862MHz	470-862MHz
Gain	1-25dB adj	1-20dB adj	6dB VHF / 1-20dB UHF adj	1-20dB adj
Noise Max	<2.5dB	<2.5dB	<2.5dB	<2.5dB
Max. Output *	102dB μ V	94dB μ V	94dB μ V	94dB μ V
Power Requirement	40mA	40mA	40mA	40mA

* DIN 45004B 3 carriers, IMD3 - 60dB

PSF1200

Mains	230V AC \pm 10% 50Hz Fitted Mains Plug BS1363 3A rating
Line Power Out	+ 12V DC (\pm 10%) 100mA
Insertion Loss	<1dB (46-1000MHz)

Fully screened Masthead Power Supply