



ACM516

## **isys<sup>5</sup>** Cascade Multiswitches

- Input level controls
- EasyMount™ fixings
- Excellent filtering & rejection
- 4mm<sup>2</sup> Earth Bonding connection
- Available in 8, 12, 16 & 20 Outputs
- Colour Coded Inputs

### PRODUCT RANGE...

- ACM508 - 5 x 8-way Cascade Multiswitch
- ACM512 - 5 x 12-way Cascade Multiswitch
- ACM516 - 5 x 16-way Cascade Multiswitch
- ACM520 - 5 x 20-way Cascade Multiswitch

### TECHNICAL SPECIFICATION

	ACM508	ACM512	ACM516	ACM520
No. of Inputs	5	5	5	5
No. of Outputs	8	12	16	20
Frequency Range Satellite	950-2150MHz	950-2150MHz	950-2150MHz	950-2150MHz
Frequency Range Terrestrial	85-862 MHz	85-862 MHz	85-862 MHz	85-862 MHz
Frequency Range DAB	217-230 MHz	217-230 MHz	217-230 MHz	217-230 MHz
Gain SAT dB	10dB	10dB	10dB	10dB
Gain UHF dB	±5dB	±5dB	±5dB	±5dB
SAT Gain Control	0-10dB	0-10dB	0-10dB	0-10dB
UHF Gain Control	±5dB	±5dB	±5dB	±5dB
Max Output Satellite*	100dBµV	100dBµV	100dBµV	100dBµV
Max Output Terrestrial*	85dBµV	85dBµV	85dBµV	85dBµV
Line powered by ASA750	120mA			

\* DIN 45004B 3 carriers, IMD<sub>3</sub> - 60dB