



isys⁵ Cascade Taps & Splitter

- IF tapped outputs - DC blocked
- EasyMount™ fixings
- 4mm² Earth Bonding connection
- 2 way Taps available in 10, 15, 20 & 25dB
- Colour Coded Inputs
- Excellent filtering & rejection

PRODUCT RANGE...

- ATT210 - 10dB 2-way Cascade Tap
- ATT220 - 20dB 2-way Cascade Tap
- ACS525 - 2-way Cascade Splitter
- ATT215 - 15dB 2-way Cascade Tap
- ATT225 - 25dB 2-way Cascade Tap

TECHNICAL SPECIFICATION

	ATT210	ATT215	ATT220	ATT225	ACS525
No. of Inputs	5	5	5	5	5
No. of Outputs	2 x 5	2 x 5	2 x 5	2 x 5	2 x 5
Frequency Range Satellite	950-2150MHz	950-2150MHz	950-2150MHz	950-2150MHz	950-2150MHz
Frequency Range Terrestrial	85-862 MHz	85-862 MHz	85-862 MHz	85-862 MHz	85-862 MHz
SAT through Loss dB	4.5dB	4.5dB	4.5dB	4.5dB	
UHF through Loss dB	4dB	4dB	4dB	4dB	
Tap Loss	10dBb	15dB	20dB	25dB	4.5dB
Satellite Tap Outputs internally DC Blocked					
Line Powered through Terrestrial Outputs with Green LED indication					
* DIN 45004B 3 carriers, IMD ₃ - 60dB					